Crystal Growth of Some Intermediate Titanium Oxide Phases γ -Ti₃O₅, β -Ti₃O₅, Ti₄O₇ and Ti₂O₃ by Chemical Transport Reactions

SAM-HYO HONG

Department of Inorganic Chemistry, Arrhenius Laboratory, University of Stockholm, S-106 91 Stockholm, Sweden

Chemical transport reactions of γ -Ti₃O₅, β -Ti₃O₅, Ti₄O₇ and Ti₂O₃ were performed in closed silica ampoules by using TeCl₄ as a transport medium. Especially, single crystals of γ -Ti₃O₅ were obtained for the first time. The previously unexplained sources of extra oxygen and oxidation introduced into the titanium oxides during transport reactions were discovered in an analysis of 53 experiments. A method is presented which predicts the oxidation state of a transported titanium oxide using empirical equations which take account of the amounts of TeCl₄, H₂O liberated from the wall of the silica ampoule, and the starting material with varied chemical compositions.

The temperature range of coexistence of the γ -Ti₃O₅ and β -Ti₃O₅ crystals was analysed. The twin crystal orientations of the β -Ti₃O₅ phase and an X-ray powder diffraction pattern yielding the refined unit cell parameters of γ -Ti₃O₅ are presented.

The polymorphism and phase transitions of Ti_3O_5 have been extensively studied by several researchers at this institute. In a phase analysis of the titanium-oxygen system it was found that the room temperature modification of a Ti_3O_5 sample prepared at 1150 °C has a monoclinic structure. The crystal structure which was later called β - Ti_3O_5 is quite different from the orthorhombic pseudobrookite-type of structure (anosovite) assigned to Ti_3O_5 some years earlier by Zhdanov and Rusakov. The pseudobrookite structure was found to exist as a high-temperature modification in the binary titanium-oxygen system (α - Ti_3O_5). The rapid reversible α - $Ti_3O_5 \rightleftarrows \beta$ - Ti_3O_5 reaction appearing at 150—

160 °C in the strictly binary system could be depressed below room temperature in the presence of impurities, e.g. iron in the case of anosovite.

The existence of a new monoclinic modification of Ti_3O_5 (called γ - Ti_3O_5 for the room temperature phase which magnetically transformed to δ - Ti_3O_5 at ca. -23 °C) was reported by Åsbrink $et~al.^4$ However, to date, single crystal growth of γ - Ti_3O_5 was unsuccessful; therefore the crystal structure, many physical properties and thermodynamical data still remain unknown.

In the course of the preparative work it was also possible to prepare crystals of β -Ti₃O₅, Ti₂O₃ and of Ti₄O₇, of which the latter is the first member of the homologous series ¹ $(4 \le n \le 10)$ Ti_nO_{2n-1}.

EXPERIMENTAL

Preparation of starting materials. As starting materials Ti_2O_3 and β - Ti_3O_5 powders were used, and these two compounds were carefully prepared in an argon atmosphere by arc-melting mixture of titanium powder (99.9 %, Ventron, USA) and titanium dioxide (99.97 %, J. T. Baker Chemical Co., USA). The titanium powder and the titanium dioxide were dried before use at 120 °C for ca. a week. The stoichiometrically mixed powders for making Ti_2O_3 and β - Ti_3O_5 were compacted at ca. 10 kbar to form pellets of 1.2 g each.

After arc-melting each pellet was finely ground in an agate mortar, and the composition was checked by means of X-ray ($CuK\alpha_1$) Guinier-Hägg powder photographs taken with a very long exposure time in order to reveal undesired phases. As starting material for further work only the

thoroughly pure samples of Ti₂O₃ (ca. 25 g) and

β-Ti₃O₅ (ca. 10 g), respectively, were retained. Silica ampoule. Schäfer et al.⁵ reported that H₂O from the wall of the silica ampoule had a decisive influence on the chemical transport rate of molybdenum and tungsten and of their dioxides and sulfides by means of iodine. According to their experience the water content in the transparent silica ampoule varied between 0.01 wt % for extremely water free silica and 0.10 wt % for ordinary grade silica.

Throughout the experiments ordinary grade transparent silica tubes (99.9 %, Thermal Syndicate Ltd., England) were used, of which the water content was estimated to be ca. 0.10 wt $\frac{9}{2}$ after cleaning in liquid soap and distilled water and drying at ca. 120 °C for several days. Ordinary grade silica glass was used as its water solubility and diffusion rate⁶ at high temperatures is known. At the same time it seemed to be very difficult to exclude traces of water even from the most water-free silica tube by heating at 900-1000 °C for a couple of days in vacuum.

Furnace. Fig. 1 shows a temperature profile of a horizontal furnace with length l=500 mm (inner diameter ID=29 mm, outer diameter OD=250 mm). An effort was made to obtain a very smooth temperature profile and a small temperature gradient in order to make possible the use of long silica ampoules (up to 200 mm) with $\Delta T = T_2 - T_1$ ≈20 °C. A Kanthal A-1 helix was carefully wound closer near both ends rather than in the central part of the furnace to yield the small temperature gradient. Sometimes three ampoules as shown in Fig. 1 were inserted for transport reactions simultaneously. The transverse temperature difference was ≤ 2 °C in the furnace.

A chromel-alumel thermocoax (stainless steel or high-melting steel sheath, OD = 1.5 mm, SODERN, France) was used with a proportional temperature




Fig. 1. Inner part of the horizontal furnace with temperature profile indicated $(-\cdot\cdot-)$. Sometimes three ampoules were simultaneously inserted.

regulator (Witronic II, Philips, Holland), which gave a temperature stability of ca. ±1 °C. At an early stage of the experiments a furnace with two Pt-Pt(Rh) thermocouples at separate temperature control points was used. It was later abandoned, however, because it did not easily yield a very smooth temperature profile.

RESULTS AND DISCUSSION

Parameters to control the oxidation state of the transported crystals.

(1) Amount of TeCl₄ and previous theories of the extra oxygen and oxidation sources. Niemysky et al.⁷ showed that above 900 °C TeCl₄ is a more effective transport agent for the TiO₂ (rutile) preparation than other halides and halogens. After that work some other oxides 8-13 were also transported by using TeCl₄. Crystals of some intermediate vanadium oxides ¹⁴⁻¹⁹ between V₂O₃ and V₂O₅ were also grown by using TeCl4. Analogously, Mercier and Lakkis 20 obtained the titanium oxides: β-Ti₃O₅, Ti₄O₇ and Ti₅O₉ (Mercier et al. only reported the composition Ti₃O₅ and the phase must be β -Ti₃O₅ according to the crystal shape and the temperatures used (ca. 1100 °C) for the chemical transport reaction).

Comparing the above two cases, of vanadium oxides and titanium oxides, there was an essential difference with regard to the compositions of the starting materials and the transported crystals. For the vanadium oxides one observed no composition changes between the starting material and the transported crystals. Even when composition changes were observed in some cases, they were usually small or within the range of homogeneity. However, for the titanium oxide transport reactions one always needed a starting material with a lower oxidation state than that of the grown crystals. In order to grow e.g. β-Ti₃O₅ one needed Ti₂O₃ as starting material; similarly, Ti₃O₅ and Ti₄O₇ were required for the growth of Ti₄O₇ and Ti₅O₉, respectively. This phenomenon was explained by a quasiequilibrium 20 in the reaction ampoule; it means that the oxygen partial pressures in the hotter zone (at T_2 , e.g. Ti_3O_5 as a starting material with the lower oxidation state) and in the colder zone (at T_1 , e.g. transported crystals of $Ti_{\Delta}O_{\tau}$ with the higher oxidation state) are the same and are equal to the corresponding equilibrium pressures above the two solid oxides, at their respective temperatures.

According to the above explanation the used temperatures T_1 and T_2 are the most significant parameters, together with the oxidation state of the starting material, determining the oxygen partial pressures in the two zones, and therefore they determine the oxidation state of the transported crystals.

No satisfactory explanation has been published which accounts for the extra oxygen and oxidation sources in the chemical transport reactions of the titanium oxides, even though the chemical transport direction and main gas species (TiCl₄, TeOCl₂, TeCl₄, TeCl₂ and Cl₂) involved in the system TiO₂:TeCl₄ were established by matrix isolation infrared spectroscopy.²¹

Recently, Since et al.²² offered a new hypothesis, stating that the extra oxygen source was probably water from the wall of the silica ampoule and the hygroscopic transport agent TeCl₄.

The experimental results from 53 careful runs (cf. Table 3), initially intended for the $\gamma\text{-Ti}_3\text{O}_5$ and $\beta\text{-Ti}_3\text{O}_5$ preparation by chemical transport reactions, showed that water could not be the sole oxidizing agent, and that a completely new explanation was required (cf. runs Nos. 29 in Table 1; 34, 36 and 52 in Table 2). Tables 1 and 2 show some typical experimental parameters: special attention was paid to water possibly adsorbed on the starting material and on the inside surface of the silica ampoule or to water in TeCl₄. The tellurium tetrachloride was stored, weighed and charged into the silica ampoule in a dry box. After charging, the

hygroscopic TeCl₄ was carefully dried by gentle heating in vacuum $(10^{-6}-5\times10^{-5} \text{ Torr}, \geq 15 \text{ hours})$ just until sublimation of TeCl₄ occured. The transport reaction of each pair of runs: Nos. 28 and 29, 40 and 41 in Table 1 were performed simultaneously as shown in Fig. 1 in order to ensure identical temperature conditions.

When the concentration of $TeCl_4$ (99.99%, Mitsuwa Chemicals, Japan) was 4.0 mg/ml or less, dark violet Ti_2O_3 crystals were transported to the colder zone, while run No. 28 yielded well-developed single phase crystals of γ - Ti_3O_5 with 7.2 mg/ml. For the two runs Nos. 28 and 29 possible H_2O amounts liberated from the wall of the silica ampoules should be exactly equal, because each pair of the ampoules used in runs Nos. 28 and 29, 40 and 41 was prepared from the same length of silica tube.

Analogously, a comparison between runs Nos. 40 and 41 and the results of further experiments with different silica ampoule volumes, but with the same concentration (mg/ml) of TeCl₄ showed that the oxidation state of the transported crystals was dependent on the input amount of TeCl₄, even though the higher concentration of TeCl₄ gives the larger amount of TeCl₄ with a similar ampoule volume (discussed later). The oxidation state of the transported titanium oxide crystals will increase with increasing amount of TeCl₄. This oxidizing effect of the transport agent TeCl₄ was also observed on the chemical transport of NbO₂ and NbO_{2.417}.²³

(2) Amounts of H_2O and of starting materials. Table 2 shows the influence of the silica ampoule

Table 1. Influence of the amount of $TeCl_4$ on the oxidation state of the transported crystals. Each pair of runs Nos. 28 and 29, 40 and 41 was simultaneously performed, as shown in Fig. 1. The abbreviations l, ID and wt stand for length, inner diameter and weight, respectively. $T_2 \rightarrow T_1$ indicates the direction of the chemical transport.

Run No.	Starting r		Ampou	le		TeCl ₄	Tem	p. (°C)	-	Residue	Transport
	(g)	(g)	l (mm)	ID (m	n) wt (g)	(mg/ml)	$T_2 \rightarrow$	· T ₁	crystals		time (day)
29	Ti ₂ O ₃ β-Ti ₃ O ₅		130	10.0	12.7	4.0	900	880	Ti ₂ O ₃	Τi ₂ O ₃ γ-Τi ₃ O ₅ β-Τi ₃ O ₅	16
28	Ti_2O_3 β - Ti_3O_5		130	10.0	12.7	7.2	900	880	γ-Ti ₃ O ₅	γ -Ti ₃ O ₅ β -Ti ₃ O ₅	16
40	Ti_2O_3 β - Ti_3O_5		145	10.0	13.5	7.8	960	910	γ-Ti ₃ O ₅	γ -Ti ₃ O ₅ β -Ti ₃ O ₅	24
41	Ti ₂ O ₃ β-Ti ₃ O ₅		145	10.0	13.5	10.1	960	910	γ-Ti ₃ O ₅ Ti ₄ O ₇	β-Ti ₃ O ₅ Ti ₄ O ₇	24

Table 2. Influence of the silica ampoule wt (H_2O content ≈ 0.001 wt) and the amount of starting material with a certain composition on the oxidation state of the transported crystals.

Run No.	U	Ampou	le		TeCl ₄	Temp	. (°C)	Transported	Residue	Transport
	(g)	l (mm)	ID (mr	n) wt (g)	(mg/ml)	$T_2 \rightarrow$	T_1	crystals		time (day)
36	Ti ₂ O ₃ 0.30							Ti ₂ O ₃	Ti ₂ O ₃	
	β -Ti ₃ O ₅ 0.10	95	10.3	7.5	7.0	940	910	β -Ti ₃ O ₅	γ -Ti ₃ O ₅	20
34	Ti ₂ O ₃ 0.60								Ti ₂ O ₃	
	β -Ti ₃ O ₅ 0.20	120	10.2	9.3	6.0	935	910	Ti_2O_3	γ-Ti ₃ O ₅	28
	, 3 3							2 3	β -Ti ₃ O ₅	
35	Ti ₂ O ₃ 0.30								γ-Ti ₃ O ₅	
	β -Ti ₃ O ₅ 0.10	130	10.2	10.1	8.0	930	908	γ -Ti ₃ O ₅	β -Ti ₃ O ₅	24
									Ti ₂ O ₃	
52	Ti_2O_3 0.50	140	10.0	10.7	6.6	1005	920	Ti_2O_3	β -Ti ₃ O ₅	9
32	Ti ₂ O ₃ 0.30								γ-Ti ₃ O ₅	
	β -Ti ₃ O ₅ 0.10	140	10.3	11.0	6.0	955	925	γ -Ti ₃ O ₅	β -Ti ₃ O ₅	8
									y-Ti ₃ O ₅	
49	Ti_2O_3 0.40	165	10.0	12.6	7.6	985	900	γ -Ti ₃ O ₅	β -Ti ₃ O ₅	21
19	Ti ₂ O ₃ 0.30								γ-Ti ₃ O ₅	
	β -Ti ₃ O ₅ 0.20	150	9.5	14.0	8.5	900	800	Ti_4O_7	β -Ti ₃ O ₅	7
									Ti ₄ O ₇	

dimensions on the oxidation state of the transported crystals. The length of the silica ampoules was varied; accordingly the weight (wt) of the silica ampoules was also varied, while the concentration of $TeCl_4$ was kept between 6.0-8.5 mg/ml. Under these conditions 18 successful runs of single phase γ -Ti₃O₅ growth were performed (cf. Table 3).

Comparing run No. 28 in Table 1 with run No. 36 in Table 2, the concentrations of TeCl₄ were almost equal to 7 mg/ml in both cases (which should give almost the same total pressure with similar temperatures), run No. 28 yielded high-quality γ -Ti₃O₅ crystals, whereas single phase Ti₂O₃ was obtained

Table 3. Specification of the 53 transport runs.

Transported crystals	Total No. of runs
γ-Ti ₃ O ₅	18
β -Ti ₃ O ₅	3
Ti ₄ O ₇	11
Ti_2O_3	12
$\gamma - Ti_3O_5 + Ti_4O_7$	4
γ -Ti ₃ O ₅ + Ti ₂ O ₃	1
β -Ti ₃ O ₅ +Ti ₂ O ₃	4

in run No. 36. One of the significant differences between the experimental parameters of the two runs was the length of the silica ampoules, which was generally expected to influence only the transport rate.²⁴ The total amounts of TeCl₄ for the two runs of Nos. 28 and 36 were 73 mg and 55 mg, respectively. This difference should also be significant, as discussed previously; and the decisive significance of the relation between the amounts of H₂O and TeCl₄ will be quantitatively discussed later.

Runs Nos. 32 and 34 in Table 2 were performed at similar temperatures and with the same concentration of TeCl₄, 6.0 mg/ml. Run No. 32 yielded single phase γ -Ti₃O₅, while No. 34 transported single phase Ti₂O₃ from twice the amount of starting material with the same composition.

The previous results and a further comparison between run No. 52 and run No. 49 clearly suggested that the oxidation state of the transported crystals was essentially dependent on the silica ampoule dimensions, the total amount of starting materials with a certain chemical composition and the input amount of TeCl₄, but not primarily dependent on the total pressure in the ampoule.

The oxidation state of the transported crystals was raised by increasing the input amount of TeCl₄ and the ampoule weight; the oxidation state was lowered by increasing the total amount of starting material.

In all 53 runs the ampoules, which had been quenched in water, emitted strongly concentrated white fumes of HCl upon breaking after the transport reaction. Addition of a water volume equal to that of the ampoule yielded a HCl solution with pH≈1. However, in the chemical transport reactions of V_3O_5 (starting material = V_3O_5 , T_1 = 950 °C and $T_2 = 1050$ °C) performed under the same experimental conditions, neither these white fumes of HCl nor Te metal (discussed below) was observed. The hydrogen source of HCl must be H₂O from the wall of the silica ampoule, because the starting materials and TeCl4 were carefully dried before use, and especially the starting materials had no contact with hydrogen gas during the preparation. Exactly the same phenomenon was observed by Mercier et al.20 in the chemical transport reactions of titanium oxides by using TeCl₄; however, they assumed the source of hydrogen to be their starting materials, which were obtained by reduction of TiO₂ by hydrogen gas.

A large amount of silvery white tellurium metal $(b.p. = 989.8 \pm 3.8 \,^{\circ}\text{C})$ was always observed in the silica ampoule after quenching in water. Concerning the observed liquid and solid components in the quenched ampoule, tellurium metal in the shapes of thin plates, spheres and crystals appeared in significant amounts besides the titanium oxides (including the starting materials and transported crystals). The major portion of the Te metal was found in the colder zone, which was raised 1-2 mm above the hotter zone in order to preclude contact between liquid Te and the growing titanium oxide crystals. When ca. 8 mg γ-Ti₃O₅ was transported with $T_1 = 910 \,^{\circ}\text{C}$ and $T_2 = 955 \,^{\circ}\text{C}$, ca. 17 mg Te metal (ca. 41 % of the total input as TeCl₄) was observed in the colder zone. The transported Te metal was usually 40-50 % of the input amount. The material was not TeO₂ (m.p. = 733 °C, b.p. = 1245 °C), as earlier assumed in analogy with the rutile transport.7

One may now summarize the experimental results in the stoichiometric equation (1) for the γ -Ti₃O₅ and β -Ti₃O₅ transports using TeCl₄ as transport medium and a charge of Ti₂O₃ or a mixture of Ti₂O₃ and β -Ti₃O₅ powders as starting material.

$$3\text{Ti}_2\text{O}_3(s) + \text{H}_2\text{O}(g) + \frac{1}{2}\text{TeCl}_4(g) \rightleftarrows 2\text{Ti}_3\text{O}_5(s) + 2\text{HCl}(g) + \frac{1}{2}\text{Te}(l \text{ and } g)$$
 (1)

Eqn. (1) is not intended to explain the whole transport system. It excludes many equilibrium reactions of carrier gases (TiCl₄, TiCl₃, TeOCl₂ and etc.)²¹ and of thermal dissociation, ²⁵ e.g., TeCl₄(g) \rightleftarrows TeCl₂(g) + Cl₂(g). However, the eqn. (1) is clearly able to explain the extra oxygen and oxidation sources and to quantitatively clarify the relationship between input and output in the closed transport system of a silica ampoule. Furthermore it is capable of predicting the oxidation state of the transported crystals (discussed later in detail); this capability is most important in order to obtain a desired phase in a strictly controlled way.

When one considers eqn. (1) as a redox reaction, one may formulate a net redox reaction, eqn. (2).

$$2Ti^{3+} + \frac{1}{2}Te^{4+} \rightleftharpoons 2Ti^{4+} + \frac{1}{2}Te$$
 (2)

Hereby one can clearly see Te^{4+} (TeCl₄) as an oxidizer, and one may understand the decisive importance of the total input amount of $TeCl_4$ for the oxidation state of the transported crystals, as discussed previously (cf. Table 1). However, it seems hardly believable that $TeCl_4$ should actively function as oxidizer without the coexistence of H_2O liberated from the wall of the silica ampoule as an extra oxygen source.

Coexistence of γ -Ti₃O₅ and α -Ti₃O₅ (β -Ti₃O₅). Single crystals of γ -Ti₃O₅ were obtained in a single phase transport to the colder zone whose temperature was varied within $T_1 = 800 - 930$ °C with $\Delta T = 15 - 100$ °C. When one inspected the residue in the hotter zone (at T_2) after successful transport reactions, γ -Ti₃O₅ and α -Ti₃O₅ crystals were always found to have developed together in the temperature range 900 °C $\lesssim T_2 \leq$ 990 °C. The γ -Ti₃O₅ and β -Ti₃O₅ crystals could be easily distinguished since they have completely different shapes, as shown in Fig. 2. However, in the residue




Fig. 2. Photograph of two modifications of the Ti_3O_5 crystals. a, γ - Ti_3O_5 , black; b, β - Ti_3O_5 , black.

the crystal quality of γ -Ti₃O₅ is always much higher than that of β -Ti₃O₅.

In run No. 49 in Table 2, with $T_2 = 985$ °C, the residue consisted mostly of β -Ti₃O₅ crystals; only 2-3% was γ -Ti₃O₅ crystals, observable under the microscope, but hardly detectable by X-ray powder diffraction. The lower temperature limit of y-Ti₃O₅ and α-Ti₃O₅ coexistence in the hotter zone seems to be slightly below 900 °C, because the β-Ti₃O₅ crystals were still observed at $T_2 = 900$ °C. No experiment was done at $T_2 < 900$ °C due to too slow water diffusion 6 into the reaction room of the ampoule. A consequence of the slow water diffusion, combined with a large transport rate ($\gtrsim 3$ mg/h), is a two-phase transport or varied oxygen content in the single phase transported crystals, as the transport system takes much longer time (≥2 day) to reach a state of equilibrium. Meanwhile, a major part of the crystals would already be transported. On the other hand, at $T_2 = 990$ °C only β -Ti₃O₅ crystals were observed. One may draw a borderline at ca. 940 °C: at that temperature the

amounts of γ -Ti₃O₅ and β -Ti₃O₅ crystals in the residue were equal.

The coexistence temperature range in the colder zone seemed to be very narrow, as no trace of β -Ti₃O₅ crystals was found below $T_1 = 930$ °C; and at that temperature well-formed crystals of γ -Ti₃O₅ appeared regularly. When the two phases γ -Ti₃O₅ and Ti₄O₇ were transported simultaneously as in run No. 41 in Table 1, the temperature range of coexistence was also narrow — no trace of γ -Ti₃O₅ was found in the hotter zone at $T_2 = 960$ °C.

Prediction of the yield. Table 3 shows the results of the 53 experimental runs, which thoroughly demonstrated the decisive influence of the amounts of $TeCl_4$ and H_2O liberated from the silica ampoules upon the oxidation state of the transported crystals. Table 4 lists quantitative comparisons between the input (in) amounts of H_2O and $TeCl_4$ and those calculated (calc) to fully oxidize the starting material to Ti_3O_5 according to the empirical equation (1). The input amount of H_2O for the transport system was taken to be 0.10 wt % of the used silica

Table 4. Different combinations of Q_1 and Q_2 for the single phase transports of Ti_2O_3 , γ - Ti_3O_5 , Ti_4O_7 or for the two-phase transports of γ - Ti_3O_5 and Ti_4O_7 . See text for explanation of symbols Q_1 , Q_2 , $H_2O(\text{in})$, $H_2O(\text{calc})$, $TeCl_4(\text{in})$ and $TeCl_4(\text{calc})$.

Run No.	H ₂ O(in) (mg)	H ₂ O(calc) (mg)	Q_1	TeCl ₄ (in) (mg)	TeCl ₄ (calc) (mg)	Q_2
Ti ₂ O ₃						
29	12.7	12.5	1.02	41	93.7	0.44
34	9.3	25.0	0.37	59	187.4	0.31
36	7.5	12.5	0.60	55	93.7	0.59
52	10.7	20.9	0.51	73	156.0	0.47
γ-Ti ₃ O ₅						
11	9.6	10.2	0.94	66	76.2	0.87
28	12.7	12.5	1.02	73	93.7	0.78
30	13.7	12.5	1.10	77	93.7	0.82
32	11.0	12.5	0.88	70	93.7	0.75
35	10.1	12.5	0.81	85	93.7	0.91
40	13.5	12.5	1.08	89	93.7	0.95
43	11.0	14.2	0.77	92	106.2	0.87
45	10.3	15.9	0.65	90	118.7	0.76
49	12.6	16.7	0.75	99	125.0	0.79
γ -Ti ₃ O ₅ + Ti ₃	4O ₇					
41	13.5	12.5	1.08	115	93.7	1.23
Ti ₄ O ₇						
17	13.1	10.4(20.6)	1.26(0.64)	88	78.1(154.7)	1.13(0.57)
18	14.0	10.2(19.3)	1.37(0.73)	85	76.2(144.4)	1.12(0.59)
19	14.0	12.5(22.8)	1.12(0.61)	90	78.1(170.6)	1.15(0.53)

ampoule. Table 4 shows only runs with different combinations of the amounts of H₂O, TeCl₄ and starting materials of varied chemical compositions.

As starting material Ti_2O_3 or a mixture of Ti_2O_3 and β - Ti_3O_5 powders was used. As shown in Tables 1 and 2, single phase transport of the γ - Ti_3O_5 crystals only occurred when the residue was completely oxidized to Ti_3O_5 .

Table 4 lists the two ratios $Q_1 = m_{\rm H_2O(in)}/m_{\rm H_2O(calc)}$ and $Q_2 = m_{\rm TeCl_4(in)}/m_{\rm TeCl_4(calc)}$, with the $m_{\rm (calc)}$ -values derived from eqn. (1). The average values $Q_1 = 0.80$ and $Q_2 = 0.80$ were calculated from 18 successful single phase transport reactions of γ -Ti₃O₅ crystals (cf. Table 3) with an average temperature of 926 °C. One can hereby predict the oxidation state of the transported crystals by combining these two empirical values of Q_1 and Q_2 . When both Q_1 and Q_2 are within 0.80 ± 0.15 , one should obtain single phase γ -Ti₃O₅ or β -Ti₃O₅, assuming optimal temperature control.

In runs Nos. 28, 30 and 40 in Table 4, yielding γ -Ti₃O₅, Q_1 was slightly larger than the upper limit 0.95. However, one could still obtain the single phase transport of γ -Ti₃O₅ as long as the other ratio was kept within the range 0.80 ± 0.15 . It is quite reasonable to assume that the oxidation state of the transport system is determined by the smallest of the two values Q_1 and Q_2 .

Twelve runs yielded single phase Ti₂O₃ (cf. Table 3) when one or both of Q_1 and Q_2 were smaller than the lower limit 0.65. The yield of single phase Ti₂O₃ from the starting material, Ti₂O₃ or a mixture of Ti_2O_3 and β - Ti_3O_5 (≤ 50 wt % of the charge), was completely unexpected judged from previous theories 20,22 about the extra oxygen and oxidation sources. However, the empirical values of Q_1 and Q_2 based on eqn. (1) quantitatively predicted the yield of Ti₂O₃ crystals when the average oxidation state of the transport system was lower than Ti_3O_5 . Two phase transport of γ - Ti_3O_5 and Ti₂O₃ was especially rare. In only one of the 53 runs this happened (cf. Table 3), and then it was probably caused by the back transport step with a large $\Delta T > 200$ °C, a large temperature oscillation $(\gtrsim \pm 5 \, ^{\circ}\text{C})$ and an uneven temperature profile of the furnace. On the other hand, two phase transport of β -Ti₃O₅ and Ti₂O₃ was rather frequent (cf. Table 3). However, the β -Ti₃O₅ crystals always grew in the vicinity of the hotter zone and Ti₂O₃ in the colder zone, with $T_1 = 1060 - 1070$ °C, $\Delta T = 25 - 70$ °C and $TeCl_4(in) = 1.5 - 4$ mg/ml. When the amount of β -Ti₃O₅ (300 mg) was three times that of Ti₂O₃ (100 mg) or more in the starting material, only β -Ti₃O₅ crystals were transported to the hotter zone. This reverse transport was also observed by Westphal *et al.*²¹ with similar mean temperatures \geq 1080 °C and TeCl₄(in)=2 mg/ml in the rutile transport reactions.

Analogously one can predict the yield of Ti_4O_7 crystals when both Q_1 and Q_2 are slightly larger than the upper limit 0.95, derived for the single phase transport of γ - Ti_3O_5 . For the single phase transport of Ti_4O_7 the additional values of Q_1 and Q_2 within parentheses in Table 4 were calculated on the assumption that the whole starting material of Ti_2O_3 and β - Ti_3O_5 was oxidized to Ti_4O_7 according to eqns. (3) and (4).

$$4\text{Ti}_2\text{O}_3(s) + 2\text{H}_2\text{O}(g) + \text{TeCl}_4(g) \rightleftarrows 2\text{Ti}_4\text{O}_7(s) + 4\text{HCl}(g) + \text{Te(l and g)}$$
(3)

$$4\text{Ti}_3\text{O}_5(s) + \text{H}_2\text{O}(g) + \frac{1}{2}\text{TeCl}_4(g) \rightleftarrows$$

 $3\text{Ti}_4\text{O}_7(s) + 2\text{HCl}(g) + \frac{1}{2}\text{Te}(l \text{ and } g)$ (4)

After single phase transport of Ti₄O₇ as well as Ti₂O₃ one always observed a large quantity of γ -Ti₃O₅ and β -Ti₃O₅ crystals in the residue together with the phase of the transported oxide, as shown in Tables 1 and 2. Surprisingly, the single phase transport of Ti₂O₃ was possible with the residue consisting of up to $80-90 \% \text{ Ti}_3\text{O}_5$ crystals. It was not possible to find a satisfactory explanation of the fact that the average oxidation state differed between transported crystals and residue in the Ti₂O₃ and Ti₄O₇ transport reactions, whereas the single phase transport of γ-Ti₃O₅ invariably required the residue to be pure Ti₃O₅. This sensitivity to the oxidation state in the transport system might be the reason why it was difficult to find optimal parameters by trial and error for the single phase transport of γ-Ti₃O₅ crystals, without a knowledge of the chemical equation (1) and the related values of Q_1 and Q_2 .

Correcting the values of Q_1 and Q_2 for the Ti_2O_3 and Ti_4O_7 growth by taking account of the amount of Ti_3O_5 in the residue, one obtains new values within the limit 0.80 ± 0.15 .

With TiO₂ (rutile), the highest oxidation state among the titanium oxides, one did not observe any difference in oxidation state between the starting material (TiO₂) and the transported crystals (TiO₂). However, the oxygen content of the transported crystals might be changed to the upper phase boundary within the homogeneity range, according to the oxidation mechanism provided by H₂O and TeCl₄.




Fig. 3. Photograph of the transported crystals. a, Ti_2O_3 , dark violet; b, Ti_4O_7 , black.

After establishing eqn. (1) and the related values of Q_1 and Q_2 derived from the 53 runs, seventeen further test runs (not included in Table 3) of the γ -Ti₃O₅ transport were performed with varied amounts and composition of the starting materials, utilizing the presented method to predict the yield. High quality crystals of single phase γ -Ti₃O₅ were invariably transported when the amounts of H₂O and TeCl₄ were adjusted to place Q_1 and Q_2 within 0.80 ± 0.15 . The concentration of TeCl₄ was kept within 6-9 mg/ml in order to produce a suitable transport rate and crystal quality.

Similar chemical equations and related values of Q_1 and Q_2 for the higher titanium oxides of the homologous series $\operatorname{Ti}_n O_{2n-1}^{-1}$ will surely serve to optimize the transport parameters, of which the combinations are otherwise numerous and often laborious to check. In such a manner it should be possible to obtain a desired phase, crystal quality and transport rate by choosing an adequate composition and amount of the starting material, dimensions of silica ampoule (not only 1 and ID but also masses are significant), total amount of TeCl_4 and temperature interval.

Description of the transported crystals. The typical crystals of γ -Ti₃O₅ and β -Ti₃O₅ are shown in Fig. 2, and the crystals of Ti₂O₃ and Ti₄O₇ are seen in Figs. 3a and 3b, respectively. The crystals of the γ -Ti₃O₅ and β -Ti₃O₅ and Ti₄O₇ phases are black. The crystals of Ti₂O₃ are dark violet. Further investigations of the hexagonal Ti₂O₃ or triclinic Ti₄O₇ crystals were not performed, because the primary interest was in the monoclinic γ -Ti₃O₅ and β -Ti₃O₅ phases.

The β -Ti₃O₅ crystals have the shape of well-developed rectangular plates with typical dimensions of ca. $0.5 \times 1.5 \times 10$ mm³. The longest edge (ca. 10 mm) was always the unique monoclinic b axis. A Weissenberg zero-level film with b as the rotation axis revealed twin formation, although the pieces of material looked like beautiful single




Fig. 4. Twin crystal orientations of the transported β -Ti₃O₅ crystals (cf. Fig. 2). One orientation of an $h \circ l$ lattice plane is drawn with solid lines ($c^* a^* b$) and the other is indicated with broken lines. The indices and the signs of the axes for the latter orientation are given within parentheses ((c^*) (a^*) (b)). \odot indicates that the positive direction of the unique monoclinic b axis is from the paper to the reader, and \otimes denotes the opposite direction (right-handed system). The horizontal lines of h and (h) indices are identical with each other. The b and (b), c^* and (c^*) orientations are coincident, respectively; however the directions are opposite. $\beta^* = 88.45^\circ$.

crystals. Fig. 4 shows the twin orientations in β -Ti₃O₅. The ratios of I (h 0 I) and I (h 0 \overline{I}) intensities were almost equal even for a small fragment broken from a large "crystal", indicating that the twin formation is of the intergrowth type.

A preliminary study of the structural transition to α -Ti₃O₅ (transition point $(t_T)\approx 150-160$ °C) was performed. When β -Ti₃O₅ was very slowly heated in a stream of hot nitrogen gas, ²⁶ the twin crystals converted to a single crystal of α -Ti₃O₅. However, the crystals used to crack when cooled again through t_T . The reason for cracking could be either a too large change of the unit cell volume in the first-order transition, or twin formation, or both. Therefore efforts to transport single crystals of β -Ti₃O₅ are now in progress by sharply optimizing the transport conditions.

Table 5. X-Ray powder diffraction pattern for the γ -Ti₃O₅ phase at 24 °C. Cu $K\alpha_1$ ($\lambda=1.540598$ Å), ²⁸ Si (a=5.431065 Å)²⁸ as an internal standard. $\Delta 2\theta=2\theta_{\rm obs}-2\theta_{\rm calc}$. Figure of merit $F_{\rm N}(=\frac{1}{|\overline{\Delta 2\theta}|}\times\frac{N}{N_{\rm poss}})$ was defined by Smith *et al.*³¹ $N_{\rm poss}=$ number of possible reflexions up to Nth observed reflexion. The refined unit cell parameters are shown in Table 6.

d _{obs} (Å)	$I_{ m obs}$	h k l	$2\theta_{\mathrm{obs}}(^{\circ})$	$\Delta 2\theta$	$F_{\rm N}(\overline{\Delta 2\theta} ,N_{\rm poss})$
4.68459	33	200	18.9288	0.0159	63 (0.0159, 1)
4.46147	12	110	19.8845	0.0070	87 (0.0115, 2)
3.37590	66	002	26.3793	0.0076	59 (0.0102, 5)
3.32780	11	-202	26.7676	0.0055	74 (0.0090, 6)
2.93048	62	-112	30.4793	0.0013	96 (0.0075, 7)
2.66133	100	310	33.6489	-0.0001	108 (0.0062, 9)
2.53663	42	020	35.3562	0.0104	103 (0.0068, 10)
2.50509	11	112	35.8164	-0.0012	119 (0.0061, 11)
2.46533	58	-312	36.4140	0.0038	127 (0.0059, 12)
2.38284	6	202	37.7214	0.0009	143 (0.0054, 13)
2.23997	(2	∫ 121	40.2278	-0.0048	122 (0.0053, 17)
2.23656	63)-411	40.2916	0.0113	115 (0.0058, 18)
2.14593	33	-213	42.0724	0.0094	107 (0.0061, 20)
2.02852	24	0 2 2	44.6344	0.0002	112 (0.0057, 22)
1.75906	51	5 1 0	51.9401	0.0007	91 (0.0053, 31)
1.73705	56	222	52.6484	-0.0017	98 (0.0051, 32)
1.72160	12	420	53.1580	0.0081	94 (0.0053, 34)
1.67143	76	-114	54.8855	-0.0086	84 (0.0055, 39)
1.64795	28	-602	55.7346	-0.0114	75 (0.0058, 44)
1.53009	8	-132	60.4545	0.0040	69 (0.0057, 51)
1.48778	16	3 3 0	62.3625	-0.0049	68 (0.0057, 54)
1.45081	67	-332	64.1383	-0.0038	67 (0.0056, 59)
1.44009	10	204	64.6733	0.0051	67 (0.0056, 61)
1.41036	18	-604	66.2093	0.0049	70 (0.0055, 62)
1.39156	27	∫-424	67.2215	0.0026	69 (0.0054, 67)
1.38924	37	512	67.3490	-0.0024	72 (0.0053, 68)

Single crystals of γ -Ti₃O₅ were 1-3 mm in both length and width, and 0.5-1.5 mm in thickness after transport periods of 7-28 days. The two best developed crystal faces were $(0\ 0\ \bar{1})$ and $(1\ 0\ 0)$. Their intersection formed a very sharp edge parallel to the unique monoclinic b axis. The angle between the faces was easily confirmed under the microscope to be $\beta^* \approx 70.1^\circ$.

Refinement of unit cell and stoichiometry control of γ -Ti₃O₅. Tables 5 shows the X-ray powder diffraction pattern for γ -Ti₃O₅ at 24 °C, of which the refined unit cell dimensions and space group are presented in Table 6 together with those of β -Ti₃O₅ ² and the high-temperature modification of V₃O₅ (high-V₃O₅).²⁷ By using a Guinier-Hägg focussing camera an optimally exposed powder film was obtained with CuK α_1 radiation (λ =1.540598 Å, ²⁸ quartz monochromator). A thin Al-foil was used to improve the S/N ratio of the powder film,

which was measured on a SAAB automatic film scanner Mk II.²⁹ The measured powder diffraction pattern of γ -Ti₃O₅ was parabolically corrected ³⁰ by five Si (a=5.431065 Å ²⁸) internal standard lines (θ <40°).

The figure of merit, $F_{\rm N}$, and $N_{\rm poss}$ in Table 5 were defined by Smith and Snyder. ³¹ $N_{\rm poss}$ means the number of possible reflexions up to the Nth observed reflexion. The powder pattern was indexed by careful comparison of the powder intensities with single crystal diffractometer data. The single crystal data were used to refine the structure ³² to a conventional R value of 0.0185 ($R_{\rm w}$ =0.0219) with an overdetermination degree of ca. 40 (number of observed independent reflexions/refined parameters 1595/40), $\sigma_{\rm Ti-Ti}$ =0.0001-0.0003 Å, $\sigma_{\rm Ti-O}$ =0.0003-0.0005 Å and $\sigma_{\rm O-O}$ =0.0004-0.0009 Å. The accuracy of the crystal structure determination and of the unit cell refinement ($\sigma(a_i)/a_i$ =5-6×10⁻⁵,

Table 6. Comparison of the unit cell parameters and space groups of γ -Ti ₃ O ₅ , β -Ti ₃ O ₅ ² and high-V ₃ O ₅ .	Table 6. Comparison of the unit ca	ell parameters and space gro	ups of γ-Ti ₃ O ₅ , β-Ti ₃ O	$_{5}^{2}$ and high- $V_{3}O_{5}^{27}$
--	------------------------------------	------------------------------	---	--

DOM:	γ -Ti ₃ O ₅ at 24 °C	β -Ti ₃ O ₅ at 20 °C	high-V ₃ O ₅ at 185 °C
a (Å)	9.9701(5)	9.752(1)	9.846(2)
b (Å)	5.0747(3)	3.8020(5)	5.0268(4)
c (Å)	7.1810(4)	9.442(1)	7.009(1)
β (°)	109.867(4)	91.55(1)	109.536(15)
$V(\mathring{A}^3)$	341.70	349.95	326.93
Space group	<i>I 2/c</i> (No. 15)	C 2/m (No. 12)	I 2/c (No. 15)

cf. Table 6) also partly demonstrated the quality of the γ -Ti₃O₅ crystals obtained by chemical transport reactions.

Possible deviation from the stoichiometry of the γ -Ti₃O₅ crystals was carefully checked by refining the unit cell parameters for crystals transported with an extreme combination of the empirical values of Q_1 and Q_2 . No changes of the unit cell parameters larger than the measurement errors ($\leq 2\sigma$) were observed even for the γ -Ti₃O₅ crystals which were transported simultaneously with the crystals of Ti₄O₇ or Ti₂O₃. Furthermore, no differences of the unit cell parameters were observed between the vapour transported and non-vapour-transported preparation.⁴

Reports on the crystal structures of γ -Ti₃O₅³² and δ -Ti₃O₅,³³ and of the results of electric conductivity measurements will shortly appear elsewhere.

Acknowledgements. I wish to express my sincere gratitude to Professor Arne Magnéli and Dr. Stig Asbrink for their kind interest and valuable comments, and to Dr. Sven Westman for linguistic correction of the article.

I am also grateful for a grant from Stiftelsen Bengt Lundqvists Minne. This work has been supported by the Swedish Natural Science Research Council.

REFERENCES

- Andersson, S., Collén, B., Kuylenstierna, U. and Magnéli, A. Acta Chem. Scand. 11 (1957) 1641.
- Åsbrink, S. and Magnéli, A. Acta Crystallogr. 12 (1959) 575.
- 3. Zhdanov, G. S. and Rusakov, A. V. Trudy Inst. Kristallogr. Akad. Nauk. SSSR 9 (1954) 165.
- Åsbrink, G., Åsbrink, S., Magnéli, A., Okinaka, H., Kosuge, K. and Kachi, S. Acta Chem. Scand. 25 (1971) 3889.

- Schäfer, H., Grofe, T. and Trenkel, M. J. Solid State Chem. 8 (1973) 14.
- Moulson, A. J. and Roberts, J. P. Trans. Faraday Soc. 57 (1961) 1208.
- 7. Niemyski, T. and Piekarczyk, W. J. Cryst. Growth 1 (1967) 177.
- Sakata, T., Sakata, K., Höfer, G. and Horiuchi, T. J. Cryst. Growth 12 (1972) 88.
- Wolf, E. and Oppermann, H. Wisse. Ber. Zentralinst. Festkörperphysik und Werkstofforschung 5 (1975) 30.
- Davtyan, G. D. Sov. Phys. Crystallogr. 21 (1976) 499.
- Gerlach, U. and Oppermann, H. Z. Anorg. Allg. Chem. 429 (1977) 25.
- Gerlach, U. and Oppermann, H. Z. Anorg. Alla. Chem. 432 (1977) 17.
- 13. Ritschel, M., Oppermann, H. and Mattern, N. *Krist. Tech.* 13 (1978) 1421.
- Bando, Y., Nagasawa, K., Kato, K. and Takada,
 T. Jpn. J. Appl. Phys. 8 (1969) 633.
- 15. Nagasawa, K. Mater. Res. Bull. 6 (1971) 853.
- Saeki, M., Kimizuka, N., Ishii, M., Kawada, I., Nakano, M., Ichinose, A. and Nakahira, M. J. Cryst. Growth 18 (1973) 101.
- 17. Oppermann, H., Stöver, G. and Wolf, E. Z. Anorg. Allg. Chem. 410 (1974) 179.
- Oppermann, H., Reichelt, W. and Wolf, E. J. Cryst. Growth. 31 (1975) 49.
- Oppermann, H., Reichelt, W., Krabbes, G. and Wolf, E. Krist. Tech. 12 (1977) 919.
- 20. Mercier, J. and Lakkis, S. J. Cryst. Growth 20 (1973) 195.
- Westphal, G. H. and Rosenberger, F. J. Cryst. Growth 49 (1980) 607.
- Since, J., Ahmed, S. and Mercier, J. J. Cryst. Growth 40 (1977) 301.
- 23. Ritschel, R. and Oppermann, H. Krist. Tech. 13 (1978) 1035.
- 24. Schäfer, H. Chemical Transport Reactions, Academic, New York 1964.
- Oppermann, H. Z. Anorg. Allg. Chem. 434 (1977) 239.
- 26. Hong, S.-H. and Åsbrink, S. J. Appl. Crystallogr. 14 (1981) 43.

- 27. Hong, S.-H. and Åsbrink, S. 4th European Crystallographic Meeting, Oxford 1977, Abstracts B, p. 575; Acta Crystallogr. B 38 (1982). In press.
- 28. Deslattes, R. D. and Henins, A. Phys. Rev. Lett. 31 (1973) 972.
- 29. Abrahamsson, S. J. Sci. Instrum. 43 (1966) 931.
- 30. Malmros, G. and Werner, P. E. Acta Chem. Scand. 27 (1973) 493.
- 31. Smith, G. S. and Snyder, R. L. J. Appl. Crystallogr. 12 (1979) 60.
- 32. Hong, S.-H. and Åsbrink, S. Acta Crystallogr. To be published.
- 33. Hong, S.-H. and Åsbrink, S. Acta Crystallogr. To be published.

Received June 16, 1981.